

Johnny Ø 80 No Trim 1L Round

Designed by FLOS Architectural, 2016



No Trim recessed luminaire with LED light source. Power supply included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	6.2
Source flux (lm)	600
System flux (lm)	399

Physical

Color	Black
Trim	Yes
Longitudinal tilting (°)	40
Transversal tilting (°)	40
Package volume (in)	916
IP internal	20



Download

Family spec sheetZIP


Mounting instructionsPDF

Photometric Files

LDT / IESZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	277
LED current (mA)	500
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable 1-10V

Notes

Class 2 Listed

Accessories & Power Supply




REQUIRED
Frame

Installation

08.9102.00

Installation frame No Trim



OPTIONAL
Housing and Hanger Bar

TRAY-0016

Registration Tray - non electrical,
place holder for non IC new
construction Round, Ø4'''

Johnny 80 No Trim 1L Square

Designed by FLOS Architectural, 2016



No Trim recessed luminaire with LED light source. Power supply included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	6.2
Source flux (lm)	600
System flux (lm)	399

Physical

Color	Black
Trim	Yes
Longitudinal tilting (°)	40
Transversal tilting (°)	40
Package volume (in)	916
IP internal	20



Download


- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files

- LDT / IES [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11


Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	277
LED current (mA)	500
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable 1-10V

Notes

Class 2 Listed

Accessories & Power Supply




REQUIRED
Frame

Installation

08.9103.00

Installation frame No Trim



OPTIONAL
Housing and Hanger Bar

TRAY-0019

Registration Tray - non electrical,
place holder for non IC new
construction, Ø4.75"

Johnny 80 No Trim 2L Square

Designed by FLOS Architectural, 2016



No Trim recessed luminaire with LED light source. Power supply included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light sources included	N
LED type	Power LED
Number of lamps	2
Power (W)	6.2
Source flux (lm)	600
System flux (lm)	399

Physical

Color	Black
Longitudinal tilting (°)	40
Transversal tilting (°)	40
Package volume (in)	N
IP internal	20



Download


- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files

- LDT / IES [ZIP](#)



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	277
LED current (mA)	500
Dimmable	Yes
Dimming type	Dimmable 1-10V

Notes

Class 2 Listed

Accessories & Power Supply



REQUIRED
Frame

08.9105.00

Installation frame No Trim



OPTIONAL
Housing and Hanger Bar

TRAY-0003

Registration Tray - non electrical,
place holder for non IC new
construction, Johnny 80 2 Lights
Trim, 2.95 x 5.79"