



Aura

Joan Gaspar


marset

This decorative lamp, which provides outstanding light while turn on but stands out beautifully while off as well, was inspired by the traditional glass carafe, a mainstay of households the world over.

The Aura follows an emotional design, because of what glass means in the collective memory, as well as a rational and contemporary design because it draws on LED technology to achieve efficiency and subtlety.



Aura

Code	Finish	Dimming	Electrical	
A676-008 A676-009 A676-010 A676-012	☐ Transparent ☐ Opal ☐ Smoked ☐ Copper	No No No No	Electrical Rating: 90-264VAC 50-60Hz 8.7W	
A676-040-50-27K A676-040-51-27K A676-040-53-27K A676-040-55-27K	☐ Transparent ☐ Opal ☐ Smoked ☐ Copper	TRIAC-ELV TRIAC-ELV TRIAC-ELV TRIAC-ELV	TRIAC-ELV (3-100%) Electrical Rating: 120-277VAC 50-60Hz 8.7W	ON-OFF LED driver dimensions: 2 3/8 x 1 1/4 x 1 3/8 inch. Dimmable LED driver dimensions: 3 x 1 1/4 x 1 3/8 inch.
A676-041-50-27K A676-041-51-27K A676-041-53-27K A676-041-55-27K	☐ Transparent ☐ Opal ☐ Smoked ☐ Copper	0-10V 0-10V 0-10V 0-10V	0-10V (0.1-100%) Electrical Rating: 120-277VAC 50-60Hz 8.7W	
Materials Shade: Blown Glass Structure: Polycarbonate Dissipater: Aluminum			Luminaire: 448lm CCT: 2700K CRI: 90	


Product Notes: Wall and ceiling mount
Structure in black, except for the opal version, with structure in white.

Suitable for damp locations


LED included



Aura Plus

Code	Finish	Dimming	Electrical	 ON-OFF LED driver dimensions: 2 3/8 x 1 1/4 x 1 3/8 inch. Dimmable LED driver dimensions: 3 x 1 1/4 x 1 3/8 inch.
A676-019	○ Transparent	No	On/Off	
A676-020	● Opal	No	Electrical Rating: 90-264VAC 50-60Hz 8.7W	
A676-021	● Smoked	No		
A676-022	● Copper	No		
A676-042-50-27K	○ Transparent	TRIAC-ELV	TRIAC-ELV (3-100%)	
A676-042-51-27K	● Opal	TRIAC-ELV	Electrical Rating: 120-277VAC 50-60Hz 8.7W	
A676-042-53-27K	● Smoked	TRIAC-ELV		
A676-042-55-27K	● Copper	TRIAC-ELV		
A676-043-50-27K	○ Transparent	0-10V	0-10V (0.1-100%)	
A676-043-51-27K	● Opal	0-10V	Electrical Rating: 120-277VAC 50-60Hz 8.7W	
A676-043-53-27K	● Smoked	0-10V		
A676-043-55-27K	● Copper	0-10V		
Materials			Luminaire: 448lm	
Shade: Blown Glass			CCT: 2700K	
Structure: Polycarbonate			CRI: 90	
Dissipater: Aluminum				

Product Notes: Wall and ceiling mount
Structure in black, except for the opal version, with structure in white.
Suitable for damp locations



⚠ WARNING. California Proposition 65 Warning for California Consumers. This product can expose you to chemicals including wood dust and lead which are known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

marsetusa@marset.com
www.marset.com

Download
Photometric data file (LDT or IES)
2D, 3D, Photometric Data
Assembly instructions