

Flauta H225 Riga


Designed by Patricia Urquiola, 2020



12W - 493lm - 2700K - CRI> 95

Wall-mounted lamp emitting dual light. Aluminium body with vertical line etching, treated with chemical conversion for resistance to atmospheric agents and powder coated to QUALICOAT standard. Deflector accessory painted to match body, installable on top or bottom head for decorative reflected light.

Designed by Patricia Urquiola, Flauta brings a sculptural quality to architectural lighting. Inspired by the pure shapes of musical instruments, each cylindrical body houses a reflector that captures and reverberates light with subtle elegance. Available in multiple sizes, textures and colours, the collection offers versatility and customisability, resulting in a luminous presence equally suited to contract spaces and domestic interiors.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Download

Mounting instructions



Main specifications

EAN	8059607030912
Mounting	Wall
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	12
System power (W)	12
Source flux (lm)	493lm
System flux (lm)	493

Physical

Color	White
Net weight (lb)	1.76
Gross weight (lb)	2.87
Package volume (in)	437.48
IP internal	40
IP external	40



Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Driver	Integrated
Dimming type	Dimmable DALI 1, Dimmable Push
Dimming interface	Dimmer Integrated
Batteries inside	No


Flauta H500 Riga

Designed by Patricia Urquiola, 2020

12W - 493lm - 2700K - CRI> 95

Wall-mounted lamp emitting dual light. Aluminium body with vertical line etching, treated with chemical conversion for resistance to atmospheric agents and powder coated to QUALICOAT standard. Deflector accessory painted to match body, installable on top or bottom head for decorative reflected light.

Designed by Patricia Urquiola, Flauta brings a sculptural quality to architectural lighting. Inspired by the pure shapes of musical instruments, each cylindrical body houses a reflector that captures and reverberates light with subtle elegance. Available in multiple sizes, textures and colours, the collection offers versatility and customisability, resulting in a luminous presence equally suited to contract spaces and domestic interiors.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Download

Mounting instructions



Main specifications

EAN	8059607030943
Mounting	Wall
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	12
System power (W)	12
Source flux (lm)	493lm
System flux (lm)	493

Physical

Color	White
Net weight (lb)	3.31
Gross weight (lb)	4.85
Package volume (in)	747.54
IP internal	40
IP external	40



Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Driver	Integrated
Dimming type	Dimmable DALI 1, Dimmable Push
Dimming interface	Dimmer Integrated
Batteries inside	No


Flauta H1000 Riga

Designed by Patricia Urquiola, 2020

12W - 493lm - 2700K - CRI> 95

Wall-mounted lamp emitting dual light. Aluminium body with vertical line etching, treated with chemical conversion for resistance to atmospheric agents and powder coated to QUALICOAT standard. Deflector accessory painted to match body, installable on top or bottom head for decorative reflected light.

Designed by Patricia Urquiola, Flauta brings a sculptural quality to architectural lighting. Inspired by the pure shapes of musical instruments, each cylindrical body houses a reflector that captures and reverberates light with subtle elegance. Available in multiple sizes, textures and colours, the collection offers versatility and customisability, resulting in a luminous presence equally suited to contract spaces and domestic interiors.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Download

Mounting instructions



Main specifications

EAN	8059607030967
Mounting	Wall
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	12
System power (W)	12
Source flux (lm)	493lm
System flux (lm)	493

Physical

Color	White
Net weight (lb)	5.95
Gross weight (lb)	8.38
Package volume (in)	1290.29
IP internal	40
IP external	40



Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Driver	Integrated
Dimming type	Dimmable DALI 1, Dimmable Push
Dimming interface	Dimmer Integrated
Batteries inside	No