

Workmates Track Large High Efficiency

Designed by FLOS Architectural, 2023



12.5W - 1386lm - 3000K - CRI> 90 - Beam° 66

Luminaire for use on The Running Magnet system. High-efficiency light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant. Casambi, máximo distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	Top LED
Number of lamps	1
Power (W)	12.5
Source flux (lm)	1682
System flux (lm)	1386

Physical

Color	Black
Orientation	Fixed
Rotation (°)	360
Length (in)	388
IP internal	20



Download

- Family spec sheetZIP
- Mounting instructionsPDF

Photometric Files


- LDT / IESZIP

Technical Drawings

- 2DZIP
- 3DZIP



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Rf fidelity index	87
Rg gamut index	103
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Beam angle C0-180 (°)	66
Beam angle C90-270 (°)	65
Extreme cut off	Yes
UGRL	<16

Electrical


Insulation class	III
Main voltage (Vac)	24
Forward voltage (V)	12
LED current (mA)	900
Driver	Remote
Dimmable	No
Dimming type	Non Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Before placing your order, please consult the product details also on the catalogue, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this site or that could be relevant to your specific project or installation.

Workmates Track Large Full Spectrum

Designed by FLOS Architectural, 2023



12.5W - 1015lm - 3000K - CRI> 98 - Beam° 66

Luminaire for use on The Running Magnet system. High-efficiency light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant. Casambi, máximo distance between fixtures: 50m.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	Top LED
Number of lamps	1
Power (W)	12.5
Source flux (lm)	1245
System flux (lm)	1015

Physical

Color	Black
Orientation	Fixed
Rotation (°)	360
Length (in)	388
IP internal	20



Download

- Family spec sheetZIP
- Mounting instructionsPDF

Photometric Files


- LDT / IESZIP

Technical Drawings

- 2DZIP
- 3DZIP



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	98
Rf fidelity index	97
Rg gamut index	101
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Beam angle C0-180 (°)	66
Beam angle C90-270 (°)	65
Extreme cut off	Yes
UGRL	<16

Electrical


Insulation class	III
Main voltage (Vac)	24
Forward voltage (V)	12
LED current (mA)	900
Driver	Remote
Dimmable	No
Dimming type	Non Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Before placing your order, please consult the product details also on the catalogue, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this site or that could be relevant to your specific project or installation.