

Tube

Design by Ichiro Iwasaki

VIBIA



Tube is a modular pendant and ceiling system with numerous possibilities. Composed of four different size of shades and a black tube that can grow in vertical and horizontal as desired, to bring the light where it is needed in groupings that are integrated with the architecture of the spaces where they are featured.

References:

6160. 6165.

Application:

Hanging Lamps.

Installation type:

Surface.

Diffuser:

Polycarbonate.

Materials:

Diffuser: Polycarbonate.

Shade: Aluminum.

Led support: Aluminum.

Tube: Steel. Black finish.

Canopy: Steel.

Finish:

- 10 White (NCS S 0300-N)
- 15 Grey L2 (NCS S 2500-N)
- 16 Grey M1 (NCS S 4500-N)
- 21 Grey D1 (NCS S 7000-N)
- 24 Beige M1 (NCS S 2005-Y50R)
- 37 Terra Red (NCS S 4040-Y70R)

Dimming: 0-10V, DALI

Personalization options available

- Configuration layout at vibia.com


Min. quantity, upcharge and extra lead time apply.

Installation and assembly:

Please, see the installation manual.

www.vibia.com ► Professional areal

and together with the product you'll receive a personalized installation guide with all the details of your composition and guidance for its correct and easy installation.




Light distribution:

Accent lighting: Fixtures providing down light to highlight a specific area or element.



Certificates:




Tube

Design by Ichiro Iwasaki



6160



1 x LED PLATE 10.5W 700mA.
LED 2700 K. CRI >90. 1170 lm.
 3000 K CRI>90 - 1251 lm
 3500 K CRI>90 - 1251 lm

Driver Constant Current 700 mA.
 120-277V. 50/60Hz.
Dimming: 0-10V.DALI-2

Installation type: Surface. Recessed.


Personalization options available

- Finish personalization
- Configuration layout at vibia.com

Min. quantity, upcharge and extra lead time apply.

LED IP20  Multi-volt 

6165



1 x LED PLATE 13.5W 700mA.
LED 2700 K. CRI >90. 1170 lm.
 3000 K CRI>90 - 1251 lm
 3500 K CRI>90 - 1251 lm

Driver Constant Current 700 mA.
 120-277V. 50/60Hz.
Dimming: 0-10V.DALI-2

Installation type: Surface. Recessed.

Personalization options available

- Finish personalization
- Configuration layout at vibia.com

Min. quantity, upcharge and extra lead time apply.

LED IP20  Multi-volt 

VIBIA, INC.

USA & CANADA
 272 Fernwood Ave.
 Edison, NJ 08837. USA
 Phone 732 417 1700.

HEADQUARTERS
 Progrés 4-6
 08850 Gavà
 Barcelona, Spain

Tube

Design by Ichiro Iwasaki

Tube is a modular pendant and ceiling system with numerous possibilities. Composed of four different size of shades and a black tube that can grow in vertical and horizontal as desired, to bring the light where it is needed in groupings that are integrated with the architecture of the spaces where they are featured.

References:

6100. 6105.

Application:

Ceiling Lamp.

Installation type:

Surface.

Diffuser:

Polycarbonate.



Materials:

Diffuser: Polycarbonate

LED support: Aluminum

Shade: Aluminum

Canopy: Steel.

Finish:

Ref. 6100, 6105

-  10 White (NCS S 0300-N)
-  15 Grey L2 (NCS S 2500-N)
-  16 Grey M1 (NCS S 4500-N)
-  21 Grey D1 (NCS S 7000-N)
-  24 Beige M1 (NCS S 2005-Y50R)
-  37 Terra Red (NCS S 4040-Y70R)

Dimming: 0-10V. DALI.

Personalization options available

- Configuration layout at vibia.com

-

Min. quantity, upcharge and extra lead time apply.

Installation and assembly:

Please, see the installation manual.

www.vibia.com ► Professional area


and together with the product you'll receive a personalized installation guide with all the details of your composition and guidance for its correct and easy installation.



Light distribution:

Accent lighting: Fixtures providing down light to highlight a specific area or element.




Certificates:

Tube

Design by Ichiro Iwasaki



6100



1 x LED PLATE 13.5W 700mA.

LED 2700 K CRI>90 - 1476 lm
3000 K CRI>90 - 1521 lm
3500 K CRI>90 - 1550 lm


Driver Constant Current 700 mA.
120-277V. 50/60Hz.

Dimming: 0-10V. DALI-2


Installation type: Surface.

Personalization options available

- Configuration layout at
vibia.com
Min. quantity, upcharge and extra
lead time apply.



6105



1 x LED PLATE 20W 700mA.

LED 2700 K CRI>90 - 2413 lm
3000 K CRI>90 - 2485 lm
3500 K CRI>90 - 2533 lm


Driver Constant Current 700 mA.
120-277V. 50/60Hz.

Dimming: 0-10V. DALI-2

Installation type: Surface.

Personalization options available

- Configuration layout at
vibia.com
Min. quantity, upcharge and extra
lead time apply.



VIBIA, INC.

USA & CANADA
272 Fernwood Ave.
Edison, NJ 08837. USA
Phone 732 417 1700.

HEADQUARTERS
Progrés 4-6
08850 Gavà
Barcelona, Spain